


## Tranzactii (utilizare programare pe partea de client):



### Buton 2 – Fara tranzactie:

```
private void button2_Click(object sender, System.EventArgs e)
{
    con.ConnectionString=conectionString;
    if(con.State != ConnectionState.Open)
    {
        con.Open();
    }

    try
    {

        OleDbParameter id = new OleDbParameter();
        OleDbParameter nume = new OleDbParameter();
        OleDbParameter salar = new OleDbParameter();
        OleDbParameter prima= new OleDbParameter();
```

```
        OleDbParameter id_2= new OleDbParameter();

        string adaugare1 = "INSERT INTO tabel1 values(?, ?, ?)";
        string adaugare2 = "INSERT INTO tabel2 values(?, ?)";
        cm1 = new OleDbCommand(adaugare1, con);
        cm2 = new OleDbCommand(adaugare2, con);

        cm1.Parameters.Add(id);
        cm1.Parameters.Add(nume);
        cm1.Parameters.Add(salar);

        cm2.Parameters.Add(id_2);
        cm2.Parameters.Add(prima);

        id_2.Value=textBox1.Text;
        id.Value = textBox1.Text;
        nume.Value = textBox2.Text;
        salar.Value = textBox3.Text;
        prima.Value = textBox4.Text;

        cm2.ExecuteNonQuery();
        cm1.ExecuteNonQuery();
        //con.Close();

    }
    catch(OleDbException ex)
    {
        Debug.Assert(false, ex.ToString());
        //MessageBox.Show(ex.ToString());
    }
    finally
    {
        if(con.State != ConnectionState.Closed)
        {
            con.Close();
        }
    }
}
```

### Buton 1 – Cu tranzactie:

```
private void button1_Click(object sender, System.EventArgs e)
{
    OleDbTransaction tran;
    con.ConnectionString=conectionString;
    if(con.State != ConnectionState.Open)
    {
        con.Open();
    }
    tran = con.BeginTransaction();

    try
    {
        OleDbParameter id = new OleDbParameter();
        OleDbParameter nume = new OleDbParameter();
        OleDbParameter salar = new OleDbParameter();
        OleDbParameter prima= new OleDbParameter();
        OleDbParameter id_2= new OleDbParameter();

        string adaugare1 = "INSERT INTO tabell1 values(?, ?, ?)";
        string adaugare2 = "INSERT INTO tabel2 values(?, ?)";
        cm1 = new OleDbCommand(adaugare1, con,tran);
        cm2 = new OleDbCommand(adaugare2, con, tran);

        cm1.Parameters.Add(id);
        cm1.Parameters.Add(nume);
        cm1.Parameters.Add(salar);

        cm2.Parameters.Add(id_2);
        cm2.Parameters.Add(prima);

        id_2.Value=textBox1.Text;
        id.Value = textBox1.Text;
        nume.Value = textBox2.Text;
        salar.Value = textBox3.Text;
        prima.Value = textBox4.Text;

        cm2.ExecuteNonQuery();
        cm1.ExecuteNonQuery();

        tran.Commit();
    }
    catch(Exception ex)
    {
        MessageBox.Show(ex.Message.ToString());
        try
```

```
        {
            tran.Rollback();
        }
        catch(Exception exx)
        {
            MessageBox.Show(exx.ToString());
        }
    }
    finally
    {
        if(con.State != ConnectionState.Closed)
        {
            con.Close();
            cm1.Dispose();
            cm2.Dispose();
        }
    }
}
```